

About Us

Mytho gained a large experience in the water treatment and chemical analysis.

Beside the design, manufacturing and distribution of its products, Mytho is specialized in developing specific customized products, with a high degree of personalisation. OEM is also an important part of its business.

Well known for the quality and

service provided, Mytho is today an ideal partner for the most demanding customers.

From the early beginning, Mytho has been specialized in the design and manufacturing of

Solenoid Metering Pumps

Motor Driven Metering Pumps (Spring and Positive return)

Research & Development

Research and Development is the heart of Mytho. A team of skilled engineers develops all its products according to customers specifications.

No compromise on quality and top brand selection of every component, yet the R&D takes care of all aspects of the design in

order to obtain the best compromise between cost and reliability. Parametric softwares

PRO-Engineering 3D

All products are developed in compliance with the stringent regulations of

CE and ATEX

Our Customers



Company Profile

Solenoid Metering Pumps

The H series of microprocessor solenoid metering pumps include different models with specific features for any kind of application. With a solid PTFE diaphragm, a PVDF liquid end and ceramic balls, this unique range of pumps are fully dedicated to the water treatment and industrial field. The stabilized electronic circuit 100:240 Vac 50/60Hz make this pump ideal for installation in any country regardless the local available power supply. Models include analogic and digital interface.

- **Pressure**
up to 20 bar

- **Flow rate**
from 0,4 to 54 l/h

- **Protection degree**
IP65

- **Liquid end**
PVDF



Motor Driven Metering Pumps

Plunger and mechanical diaphragm range of metering pumps with spring return mechanism.

Standard liquid ends available in PP, PVC, PVDF and SS 316L.

Plungers available in Ceramic and SS 316L, diaphragm in PTFE.

Manual adjustable flow rate, electric and pneumatic.

A complete selection of accessories including safety and backpressure valves, pulsation dampers and filters allow a correct installation.

- **Pressure**
up to 200 bar

- **Flow rate**
from 1,5 to 1000 l/h

- **Fluid temperature**
- SS 316 pump head: 40° C
- PP pump head: 40° C

- **Liquid end**
- SS 316L
- PP
- PVC
- PVDF



Motor Driven API675 Metering Pumps

A complete range of plunger and hydraulic double diaphragm metering pumps, designed according to API 675 standards. A wide selection of liquid end materials allow this range to be installed in almost any heavy duty application. All models comply with the ATEX specification, for installation in hazardous explosion proof areas. Accessories include automatic electrical and pneumatic stroke regulation, heating and cooling head, leak detection remote control.

- **Pressure**
up to 200 barg

- **Flow rate**
up to 2650 l/h with single head

- **Fluid temperature**
from -10 °C to 90 °C

- **Liquid end**
- SS 316L
- PP
- PVDF

